


# Ecoustic® Matrix Ceiling

—  
A highly functional acoustic modular ceiling tile that is easy to install




INSTYLE

# Ecoustic® Matrix Ceiling Tile

## Front View


600 Tile: 595 x 595mm



## Side View

## Front View

1200 Tile: 1195 x 595mm



## PRODUCT

Ecoustic® Matrix Ceiling Tile

## DESCRIPTION


Highly functional sound absorbent suspended ceiling tile designed for new and existing suspended ceilings

## DIMENSIONS

600 Tile: 595mm (w) x 595mm (h) x 65mm (d)  
1200 Tile: 1195mm (w) x 595mm (h) x 65mm (d)  
Matrix Ceiling Tile drops into new or existing 15mm and 24mm Exposed Tee drop ceiling grid systems with a nominal 600 x 600mm or 1200 x 600mm grid. Ensure the tile is suitable for your selected system prior to ordering

## ACOUSTIC

$\alpha_w$  0.75(H) / NRC 0.75 (400mm airgap)



## FIRE TEST

AS/ISO 9705

Group 1  
SMOGR <100

GB8624-2012

Grade B1

## APPLICATION

ceiling tiles

## ORIGIN

Made in Australia

Please contact your representative for CAD drawings

## BENEFITS

### Designed for the Environment

- Based on low energy manufacturing
- 100% polyester (up to 32.5% PC + PI recycled content)
- Designed for disassembly + recyclable
- Low-VOC, EPD + Greentag Level A Certified

**Toxicity:** Polyester is non-toxic and is classed the same as wood under the State of New York Article 15 Part 1120. Matrix Ceiling Tile does not contain any Red List Chemicals (USA EPA).

**Warranty:** A 12 month warranty is provided against manufacturing defects. Internal installation only, outdoor use will void any warranty.

**Building Rating Systems:** Matrix will contribute the following points for Green Star, LEED + WELL building standards.


Criteria	Green Star	LEED	WELL
Recycled Content	✓	✓	NA
Low VOC	✓	✓	✓
Recycling Program	✓	✓	NA
EPD	✓	✓	NA
Third Party Greentag Level A Certification	✓	✓	✓
Toxic Material Reduction	NA	NA	✓

## HOW TO SPECIFY


DESIGN	Ecoustic® Matrix Ceiling Tile
TILE SIZE	600 Tile or 1200 Tile
COLOUR	Select from felt colours



# Ecoustic® Matrix Ceiling Tile Components



Ecoustic® Matrix Ceiling Tile  
 100% polyester (up to 32.5% recycled content)  
 8 tiles per box in a single colour



Drop Ceiling Frame  
 15mm + 24mm Exposed Tee grid system  
 [ Not supplied ]



## IMPORTANT

**Moisture Absorption:** Exposure to an atmosphere of 50% and 95% RH for four days provides moisture absorption of less than 0.2% per volume. As Ceiling Matrix is 100% polyester, it will not degrade over time due to moisture, mildew or rot in office environments.

**Fixtures:** Any fixtures must be supported independent to the tile. Ceiling Matrix can be cut on site to accommodate for new and existing lighting and fixtures. When cutting use a new blade for each cut and ensure the area to be cut is fully supported throughout. Cut from the tile face with care.

**HVAC:** Ensure Ceiling Matrix is compliant with the specified HVAC system. Ceiling Matrix is recommended for Ducted Return Air and is not Plenum Return Air rated.

**Back Loading:** Ceiling Matrix is not suitable for back loading. Loads must be supported independently by the grid or through the use of additional fixtures.

Product may vary in colour due to the nature of the media  
 Please refer to website for current colour range

Variation in fibre mix and colour is an inherent feature of this product and variation from batch to batch may occur